

# **PROBOND**classic<sup>®</sup>X30

## TYPICAL SPECIFICATION

Composite panels shall be PROBOND ClassicX30<sup>®</sup> as manufactured and supplied throughout Australia exclusively by PROBOND<sup>®</sup> Architectural.

PROBOND ClassicX30<sup>®</sup> panels shall consist of 2 face sheets of 0.30mm thick aluminium sandwiching a core of pure LDPE (low density polyethylene), formed in a continuous process.

PROBOND ClassicX30<sup>®</sup> panels shall consist of an overall thickness of 3mm.

Face sheets, unless noted otherwise, shall be pre-finished in colour selected from the PROBOND ClassicX30<sup>®</sup> standard colour range, with both sides coated using High Performance PPG Polyester paint applied by continuous coil coating process. Spray application not acceptable. Applied coating shall be protected with peelable UV stabilised PE protective film.

All PROBOND ClassicX30<sup>®</sup> panels prior to fabrication shall be stored horizontally on a dry, flat, level surface and protected from damage from other trades.

Fabrication techniques as recommended by PROBOND<sup>®</sup> Architectural shall be strictly adhered to. These include cutting, grooving, folding, bending and rolling. Information concerning these techniques can be obtained from PROBOND<sup>®</sup> Architectural.