

PROGRIP™

Go-to Solution for Superior Adhesion

PROGRIP is made for Australian construction, ensuring resilient, waterproof bonds on diverse materials. Ideal for glazing, industrial, and automotive applications, offering durability and reliability.

PROGRIP™ MS Adhesive



PROGRIP™ MS Adhesive

PROGRIP MS500 is a premium high-performance adhesive and sealant, based on MS polymer technology, specifically crafted for the Australian construction industry. It forms a resilient, waterproof bond on diverse materials, serving as both a high-strength adhesive and a highly durable joint sealant. Tailored to meet the high standards of professionals, PROGRIP ensures superior adhesion and durability in various construction applications.

Designed for sealing and bonding in the building and construction industry, PROGRIP excels in accommodating various substrates commonly used in construction. From metals (aluminium, steel, etc.) to glass, wood, brick, concrete, and PVC, PROGRIP is perfect for applications like facades, out frames, ceramics, windows, and more.

Ideal use:

- Suitable for use as a bondbreaker, for all RLA Acrylic membranes.
- Elastic bonding in vibrating constructions.
- Concrete expansion joints.
- Sealing where acoustic properties are required.
- Perimeter sealing around window and door frames.
- Sealing of penetrations in walls or floors.
- Brickwork, ceramics, stone, granite & marble.
- Sanitary applications.
- Other substrates including anodized aluminium, steel, glass, dry timbers, some tiles, treated wood, PVC, and plastics

SPECIFICATIONS

Packaging Option	Tube
Colour	Grey
Size	300ml
Qty per Carton	24
Cure Type	Neutral Cure Hybrid
Skin Time	10 mins
Tack Free	20 mins
Tensile Strength	3.5 MPa
Hardness	50
Application Temperature	5°C - 40°C
Uses	Interior / Exterior

PROGRIP™ Supa-Seal



PROGRIP™ Supa-Seal

PROGRIP SS20 is an industrial-grade 100% neutral curing silicone adhesive/sealant, meticulously crafted for versatile applications in general-purpose glazing, industrial settings, and automotive sealing. This high-performance, one-component neutral cure silicone sealant is specifically designed to deliver exceptional adhesion and long-term reliability, meeting the rigorous demands of various sealing requirements.

Ideal for general-purpose roofing, glazing, industrial, and automotive sealing applications where excellent adhesion and long-term reliability are imperative. PROSEAL exhibits outstanding weathering and UV resistance, ensuring durability in diverse environmental conditions.

Ideal use:

- Weather seals between glass and aluminium
- Back glazing between timber and glass
- Perimeter seals between aluminium window frames
- Brick and masonry
- Air seals in concrete panels
- General construction
- Electrical applications
- Marine work
- Industrial and maintenance applications

SPECIFICATIONS

Packaging Type	Tube
Colour	Clear, Black, White
Size	300ml
Qty per Carton	24
Cure Type	Neutral Cure Oxime
Skin Time	3 mins
Tack Free	8 mins
Tensile Strength	1.8 MPa
Hardness	27
Application Temperature	5°C - 40°C
Uses	Interior / Exterior